

DERWENT-ACC-NO: 1977-06776Y

DERWENT-WEEK: 197704

\~4~COPYRIGHT 1999 DERWENT INFORMATION LTD\~14~

TITLE: Lubricant for welding wire - contg. emulsifier, water insoluble cpd. and water

INVENTOR-NAME:

PRIORITY-DATA: 1975JP-0068787 (June 6, 1975)

PATENT-FAMILY:

PUB-NO PAGES	PUB-DATE	LANGUAGE	
MAIN-IPC			
JP 51144353 A N/A	December 10, 1976	N/A	000
JP 83054917 B N/A	December 7, 1983	N/A	000

INT-CL\_(IPC): B23K035/36

ABSTRACTED-PUB-NO: JP51144353A

BASIC-ABSTRACT: The lubricant is used in arc welding and electrogas welding Its

pH is adjusted to 7.5-10.0. It contains 4-17 wt.% of emulsified sulphuric acid

ester of high fatty acid and soap, alkali salt of higher fatty acid of >C8

resin acid or naphthenic acid alkali metal salt, alkylallylsulphonate,

alkylphenol sulphonate etc. and the remainder water, and water insol. liquid

e.g. higher fatty acid or higher alcohol >c8, having carboxyl - group or hydroxy group as hydrophilic gp.

Incorporating trace amt. of the lubricant agent on the surface of the welding

wire helps to increase the feeding capacity, corrosion and rust prevention, and

welding operation. Also a weld pt. of high quality contg. a decreased amt. of hydrogen is produced.

TIX:

Lubricant for welding wire - contg. emulsifier, water insoluble cpd. and water

ABTX:

The lubricant is used in arc welding and electrogas welding Its pH is adjusted

to 7.5-10.0. It contains 4-17 wt.% of emulsified sulphuric acid ester of high

fatty acid and soap, alkali salt of higher fatty acid of >C8 resin acid or naphthenic acid alkali metal salt, alkylallylsulphonate, alkylphenol sulphonate etc. and the remainder water, and water insol. liquid e.g. higher fatty acid or higher alcohol >c8, having carboxyl group or hydroxy group as hydrophilic gp.

ABTX:

Incorporating trace amt. of the lubricant agent on the surface of the welding wire helps to increase the feeding capacity, corrosion and rust prevention, and welding operation. Also a weld pt. of high quality contg. a decreased amt. of hydrogen is produced.

TTX:

LUBRICATE WELD WIRE CONTAIN EMULSION WATER INSOLUBLE COMPOUND WATER